


RETROFIT ANODE

PIRANHA® XL CLAMP



**“The Piranha XL® range is intended for mounting to plates.
Equipped with a jaw that covers ranges from 75 – 120 mm.”**



Intelligence built in

The main benefits of choosing an Imenco Piranha® Clamp are ease of installation, flexible sizing, and proven long-term integrity.

The clamp is guided into place by ROV and tensioned with an Imenco Clamp Installation Tool (ICIT) to ensure a good connection.

Most subsea structures and components have some sort of plate as part of its design. This makes the Piranha® M Plate Clamp the most versatile IMENCO Retrofit Anode Clamp. Anodes may be attached directly to the clamp, or by a bonding cable to an anode sled.

Piranha® XL is typically used for the placement of sacrificial anodes, electrical continuity between different entities or to connect instrument packages to a structure. Anodes may be attached directly to the clamp, or by a bonding cable to an anode sled/anode bank.

Features


- Field proven with more than 3000 clamps installed
- Simple and robust design
- Durable and compact design dimensions
- Excellent mechanical grip
- Quickly diver-less ROV installation
- Anode attachment flexibility, clamping on plate, edges or ends of rods
- Designed for variety of plate/rod thicknesses
- Standardized installation tool and ROV interface

Advantages

- Quick installation, typically takes 15min to install a clamp
- Provides excellent mechanical attachment, Typically, > 10 ton
- Provides excellent electrical contact / grounding, Typically, <100 $\mu\Omega$ connection resistance
- Mechanical grip (tension)
 - Will not loosen by vibration
 - Fatigue resistant against expected loads
- Electrical Resistance – house to connected structure
 - Can be used on coated or uncoated structures.
 - Will bite through existing rust layers on structures

Applications and options

The Piranha® Clamps has a proven track record of being easy to install and providing a very strong hold and an effective electrical connection. By use of a hydraulic torque tool, the clamps are installed onto plates or rods, consistently and without any unnecessary strain on the ROVs.



RETROFIT ANODE

PIRANHA® XL CLAMP

The Piranha® XL clamp is primarily composed of the housing, and the jaw. The housing design is suitable across the entire 75-120 mm range. The jaw size is selected on a project-specific basis as per the below table.

Clamp Type	Plate/Pipe Dim (mm)	Clamp Dimensions (mm)							Weight
		A	B	C	D	E	F	G	
Piranha XL®	75-85 mm	75	20	205	198	75-85	37-40	46	18 Kg
Piranha XL®	80-90 mm	75	20	205	198	80-90	37-40	46	18 Kg
Piranha XL®	91-95 mm	75	20	205	198	91-95	37-40	46	18 Kg
Piranha XL®	96-100 mm	75	20	205	198	96-100	37-40	46	18 Kg
Piranha XL®	115-120 mm	75	20	205	198	115-120	37-40	46	18 Kg
Piranha XL®	75-85 mm	75	20	205	198	75-85	37-40	46	18 Kg
Piranha XL®	80-90 mm	75	20	205	198	80-90	37-40	46	18 Kg
Piranha XL®	91-95 mm	75	20	205	198	91-95	37-40	46	18 Kg
Piranha XL®	90-102 mm	75	20	205	198	90-102	37-40	46	18 Kg
Piranha XL®	96-100 mm	75	20	205	198	96-100	37-40	46	18 Kg
Piranha XL®	98-108 mm	75	20	205	198	98-108	37-40	46	18 Kg

